

# Vikingmast fiberglass flagpole

## Product specifications



Flagpole height		6m	7m	8m	9m	10m	11m	12m	13m	14m
Top diameter	mm	65	65	65	65	65	65	65	65	65
Bottom diameter		120	120	120	120	140	140	140	140	140
Fiberglass thickness +/- 0,5 mm		4	4	4	4	4	4	4	4	4
Cylindrical length		0	0	0	0	2500	2500	2500	3500	4500
<b>1</b> Steel tube diameter		102	102	102	102	121	121	121	121	121
Steel tube thickness		2,5	2,5	2,5	2,5	3	3	3	3	3
Steel tube length		660	660	660	660	660	660	660	660	660
<b>2</b> Distance from bottom to to:										
- Cleat		1500	1000	1500	1500	1500	1500	1500	1500	1500
- Lock		1500	1500	1500	1500	1500	1500	1500	1500	1500
- Crank		630	630	630	630	630	630	630	630	630
Weight of fiberglass tube	kg	11,5	14,5	15,5	17,5	26,5	29	31,5	49	44,5
Weight of fiberglass tube with steelwork		17	19	21	24	34	36,5	38,5	53	53
<b>3</b> Suggested depth of ground foundation	mm	800	800	800	900	1000	1100	1200	1200	1200
Suggested diam of ground foundation		500	500	500	500	500	500	500	500	500
<b>4</b> Suggested hole diam for rock install		35	35	35	35	35	35	35	35	35
Suggested length of hole for rock install		300	300	300	400	400	400	400	400	400
Spacing between holes		168	168	168	168	168	168	168	168	168
<b>5</b> Anchor rods length		500	500	500	500	500	500	500	500	500
Anchor rods diameter		20	20	20	20	20	20	20	20	20
Recommended maximum flag size	sq m	2	2,5	3	4	5	5	6	6	6

